



(2 szt.)
skala 1:25




Položaj	Srednja dubina (m)	Lisica		Dugina (m)		
		desetljetov	općen			
1	2400	1	26	157,86		
2	16	2710	1	26	158,13	
3	16	4100	26	1	122,20	
4	16	5500	20	1	26	145,52
5	8	2260	61	1	61	117,05
Dugina po zraklo (m)					157,86	
Dugina po zraklo (m)					158,13	
Masa po zraklo (kg)					0,22	
Masa po zraklo (kg)					30,62	
Masa po zraklo (kg)					351,16	
Masa po zraklo (kg)					351,17	

(1 szt.)
skala 1:25



Poz.	Śred. Zachł.	Długość (mm)	Liczba		Długość (mm)
			w kierunku ekstremów	ogólna	
16	16	2210	16	16	45,38
17	18	4292	16	1	75,20
19	10	5503	16	1	86,32
19	6	1260	61	1	70,95
Długość w kierunku (mm)			76,86	206,88	
Masa (w grzechy) (g)			12,2	17,04	
Masa łączna w kierunku (g)			17,04	326,87	
Masa łączna w grzechy (g)			34,30		

(1 szt.)
skala 1:25



Opis (kg)	Masa (kg)	Masa (kg) na grani (kg)	Liczba		Długość (mm)
			w kierunku elektrycznym	opisem	
Procz.	24				
20	10	2710	16	1	16
21	16	4700	16	1	16
22	19	5500	16	1	16
23	6	1600	61	1	61
Długość wzdłuż (mm)					
					64,66
					206,88
Masa (kg) na grani (kg)					
					14,55
					326,87
Opisem (kg)					
					341,22

BEI ON C25/30
Stal A-III N - klasa ciągliwości
Otulina stropów i belek - 3 cm