




(2 szt.)  
skala 1:25





### Zestawienie stali dla 1 rdzenia R6

Order number	Size mm	Solid Diameter (mm)	Lubricant		Diameter (mm)
			in diameter	out diameter	
24	16	2170	26	1	26
25	16	4700	26	1	26
26	16	5500	26	1	26
27	6	2400	61	1	61
Diameter in middle (mm)			150.06	136.18	
Diameter in front (mm)			0.22		
Diameter in rear (mm)			33.37	511.16	
Mean square in diameter (mm)			664.46		




### Zestawienie stali dla 1 stupa S5a

Noj. izveštaja	Ime i prezime (naziv)	Datum izveštaja	Dugopid (mm)	Leksa		Dugopid lekara (mm)
				a - deklinacija	deklinacija	
1	1	1	28	1	28	
2	2	2	28	1	28	
3	3	3	28	1	28	
4	4	4	28	1	28	
5	5	5	28	1	28	
6	6	6	28	1	28	
7	7	7	28	1	28	
8	8	8	28	1	28	
9	9	9	28	1	28	
10	10	10	28	1	28	
11	11	11	28	1	28	
12	12	12	28	1	28	
13	13	13	28	1	28	
14	14	14	28	1	28	
15	15	15	28	1	28	
16	16	16	28	1	28	
17	17	17	28	1	28	
18	18	18	28	1	28	
19	19	19	28	1	28	
20	20	20	28	1	28	
21	21	21	28	1	28	
22	22	22	28	1	28	
23	23	23	28	1	28	
24	24	24	28	1	28	
25	25	25	28	1	28	
26	26	26	28	1	28	
27	27	27	28	1	28	
28	28	28	28	1	28	
29	29	29	28	1	28	
30	30	30	28	1	28	
31	31	31	28	1	28	
32	32	32	28	1	28	
33	33	33	28	1	28	
34	34	34	28	1	28	
35	35	35	28	1	28	
36	36	36	28	1	28	
37	37	37	28	1	28	
38	38	38	28	1	28	
39	39	39	28	1	28	
40	40	40	28	1	28	
41	41	41	28	1	28	
42	42	42	28	1	28	
43	43	43	28	1	28	
44	44	44	28	1	28	
45	45	45	28	1	28	
46	46	46	28	1	28	
47	47	47	28	1	28	
48	48	48	28	1	28	
49	49	49	28	1	28	
50	50	50	28	1	28	
51	51	51	28	1	28	
52	52	52	28	1	28	
53	53	53	28	1	28	
54	54	54	28	1	28	
55	55	55	28	1	28	
56	56	56	28	1	28	
57	57	57	28	1	28	
58	58	58	28	1	28	
59	59	59	28	1	28	
60	60	60	28	1	28	
61	61	61	28	1	28	
62	62	62	28	1	28	
63	63	63	28	1	28	
64	64	64	28	1	28	
65	65	65	28	1	28	
66	66	66	28	1	28	
67	67	67	28	1	28	
68	68	68	28	1	28	
69	69	69	28	1	28	
70	70	70	28	1	28	
71	71	71	28	1	28	
72	72	72	28	1	28	
73	73	73	28	1	28	
74	74	74	28	1	28	
75	75	75	28	1	28	
76	76	76	28	1	28	
77	77	77	28	1	28	
78	78	78	28	1	28	
79	79	79	28	1	28	
80	80	80	28	1	28	
81	81	81	28	1	28	
82	82	82	28	1	28	
83	83	83	28	1	28	
84	84	84	28	1	28	
85	85	85	28	1	28	



### Zestawienie stali dla 1 stupa S5

Opisno (kg)	Masa sušene su sirovine (kg)	Masa sušene su gotovine (kg)	Masa i težište (g)	Dugina su sirovine (m)	Širina su sirovine (m)	Dugina su gotovine (m)	Širina su gotovine (m)	Amin	
								g	%
32	16	2710	22	1	22	1	22	1	59,62
33	16	4700	22	1	22	1	22	1	10,43
34	16	3200	22	1	22	1	22	1	80,24
35	16	2400	22	1	22	1	22	1	140,38
36	16	2400	22	1	22	1	22	1	148,26
37	16	2400	22	1	22	1	22	1	148,26
38	16	2400	22	1	22	1	22	1	148,26
39	16	2400	22	1	22	1	22	1	148,26
40	16	2400	22	1	22	1	22	1	148,26
41	16	2400	22	1	22	1	22	1	148,26
42	16	2400	22	1	22	1	22	1	148,26
43	16	2400	22	1	22	1	22	1	148,26
44	16	2400	22	1	22	1	22	1	148,26
45	16	2400	22	1	22	1	22	1	148,26
46	16	2400	22	1	22	1	22	1	148,26
47	16	2400	22	1	22	1	22	1	148,26
48	16	2400	22	1	22	1	22	1	148,26
49	16	2400	22	1	22	1	22	1	148,26
50	16	2400	22	1	22	1	22	1	148,26
51	16	2400	22	1	22	1	22	1	148,26
52	16	2400	22	1	22	1	22	1	148,26
53	16	2400	22	1	22	1	22	1	148,26
54	16	2400	22	1	22	1	22	1	148,26
55	16	2400	22	1	22	1	22	1	148,26
56	16	2400	22	1	22	1	22	1	148,26
57	16	2400	22	1	22	1	22	1	148,26
58	16	2400	22	1	22	1	22	1	148,26
59	16	2400	22	1	22	1	22	1	148,26
60	16	2400	22	1	22	1	22	1	148,26
61	16	2400	22	1	22	1	22	1	148,26
62	16	2400	22	1	22	1	22	1	148,26
63	16	2400	22	1	22	1	22	1	148,26
64	16	2400	22	1	22	1	22	1	148,26
65	16	2400	22	1	22	1	22	1	148,26
66	16	2400	22	1	22	1	22	1	148,26
67	16	2400	22	1	22	1	22	1	148,26
68	16	2400	22	1	22	1	22	1	148,26
69	16	2400	22	1	22	1	22	1	148,26
70	16	2400	22	1	22	1	22	1	148,26
71	16	2400	22	1	22	1	22	1	148,26
72	16	2400	22	1	22	1	22	1	148,26
73	16	2400	22	1	22	1	22	1	148,26
74	16	2400	22	1	22	1	22	1	148,26
75	16	2400	22	1	22	1	22	1	148,26
76	16	2400	22	1	22	1	22	1	148,26
77	16	2400	22	1	22	1	22	1	148,26
78	16	2400	22	1	22	1	22	1	148,26
79	16	2400	22	1	22	1	22	1	148,26
80	16	2400	22	1	22	1	22	1	148,26
81	16	2400	22	1	22	1	22	1	148,26
82	16	2400	22	1	22	1	22	1	148,26
83	16	2400	22	1	22	1	22	1	148,26
84	16	2400	22	1	22	1	22	1	148,26
85	16	2400	22	1	22	1	22	1	148,26
86	16	2400	22	1	22	1	22	1	148,26
87	16	2400	22	1	22	1	22	1	148,26
88	16	2400	22	1	22	1	22	1	148,26
89	16	2400	22	1	22	1	22	1	148,26
90	16	2400	22	1	22	1	22	1	148,26
91	16	2400	22	1	22	1	22	1	148,26
92	16	2400	22	1	22	1	22	1	148,26
93	16	2400	22	1	22	1	22	1	148,26
94	16	2400	22	1	22	1	22	1	148,26
95	16	2400	22	1	22	1	22	1	148,26
96	16	2400	22	1	22	1	22	1	148,26
97	16	2400	22	1	22	1	22	1	148,26
98	16	2400	22	1	22	1	22	1	148,26
99	16	2400	22	1	22	1	22	1	148,26
100	16	2400	22	1	22	1	22	1	148,26



BETON C25/30  
Stal A-IIIIN - klasa ciągliwości C  
Otulina stropów i belek - 3 cm